

Model	Rated thermal power (MW)	Rated working pressure (MPa)	Rated output water temperature (°C)	Return water temperature (°C)	Maximum transport size(m) (L×W×H)
SZL2.8-0.7/95/70-M	2.8	0.7	95	70	customized size
SZL4.2-1.0/115/70-M	4.2	1	115	70	7.0×2.7×3.5
SZL5.6-1.0/115/70-M	5.6	1.0	115	70	6.9×3.2×5.3
SZL5.6-1.25/130/70-M	5.6	1.25	130	70	6.9×3.2×5.3
SZL7.0-1.0/115/70-M	7	1.0	115	70	7.9×3.3×3.5
SZL7.0-1.25/130/70-M	7	1.25	130	70	7.9×3.3×3.5
SZL14-1.0/115/70-M	14	1.0	115	70	11×3.2×3.5
SZL14-1.25/130/70-M	14	1.25	130	70	11×3.2×3.5
SZL21-1.0/115/70-M	21	1.0	115	70	9.9×3.3×3.6
SZL21-1.25/130/70-M	21	1.25	130	70	9.9×3.3×3.6
SZL29-1.0/115/70-M	29	1.0	115	70	customized size
SZL29-1.25/130/70-M	29	1.25	130	70	customized size